

STORM WATER TREATMENT

STORM WATER QUALITY UNIT

DIAMETER	LENGTH	INLET SIZE	OUTLET SIZE	TREATED FLOW RATE	PRODUCT CODE
900 mm (36")	3.7 m (12')	250 mm (10")	250 mm (10")	24 L/s (0.8 cfs)	3612WQA
900 mm (36")	3.7 m (12')	250 mm (10")	250 mm (10")	12 L/s (0.4 cfs)	3612WQB
900 mm (36")	6.1 m (20')	250 mm (10")	250 mm (10")	42 L/s (1.5 cfs)	3620WQA
900 mm (36")	12.2 m (40')	250 mm (10")	250 mm (10")	67 L/s (2.38 cfs)	3640WQA
900 mm (36")	6.1 m (20')	250 mm (10")	250 mm (10")	20 L/s (0.7 cfs)	3620WQB
900 mm (36")	12.2 m (40')	250 mm (10")	250 mm (10")	45 L/s (1.6 cfs)	3640WQB
1050 mm (42")	6.1 m (20')	300 mm (12")	300 mm (12")	49 L/s (1.79 cfs)	4220WQA
1050 mm (42")	12.2 m (40')	300 mm (12")	300 mm (12")	104 L/s (3.66 cfs)	4240WQA
1050 mm (42")	6.1 m (20')	300 mm (12")	300 mm (12")	24 L/s (0.86 cfs)	4220WQB
1050 mm (42")	12.2 m (40')	300 mm (12")	300 mm (12")	52 L/s (1.83 cfs)	4240WQB
1200 mm (48")	6.1 m (20')	300 mm (12")	300 mm (12")	64 L/s (2.26 cfs)	4820WQA
1200 mm (48")	12.2 m (40')	300 mm (12")	300 mm (12")	112 L/s (3.94 cfs)	4840WQA
1200 mm (48")	6.1 m (20')	300 mm (12")	300 mm (12")	32 L/s (1.13 cfs)	4820WQB
1200 mm (48")	12.2 m (40')	300 mm (12")	300 mm (12")	68 L/s (2.39 cfs)	4840WQB
1500 mm (60")	6.1 m (20')	375 mm (15")	375 mm (15")	84 L/s (2.95 cfs)	6020WQA
1500 mm (60")	12.2 m (40')	375 mm (15")	375 mm (15")	176 L/s (6.23 cfs)	6040WQA
1500 mm (60")	6.1 m (20')	375 mm (15")	375 mm (15")	42 L/s (1.47 cfs)	6020WQB
1500 mm (60")	12.2 m (40')	375 mm (15")	375 mm (15")	88 L/s (3.12 cfs)	6040WQB

- Add two digit number at end of product number for bypass size.
- 00 at end of product number indicates no bypass.